

TEROSON® SB 450

July 2020

PRODUCT DESCRIPTION

TEROSON® SB 450 provides the following product characteristics:

Technology	Primer and Cleaner
Chemical Type	Alcoholic Solution
Appearance	Colorless, Clear Liquid
Components	One-Component- requires no mixing
Cure	Not applicable
Application	Surface Treatment
Specific Benefits	<ul style="list-style-type: none"> • High cleaning properties • Improve adhesion on difficult-to-bond surfaces • Simple process with cleaning and priming

TEROSON® SB 450 is an alcoholic solution designed for the cleaning of difficult to bond surfaces. It contains active ingredients that improve the adhesion of elastic adhesives and sealants on surfaces on which adhesion is usually difficult to achieve.

TYPICAL PROPERTIES

Specific Gravity @ 23°C	0.8
Drying Time @ 23°C, minutes	10

TYPICAL PERFORMANCE

TEROSON® SB 450 is used for cleaning and if necessary, to improve adhesion of elastic adhesives and sealants on metals, plastics, and coated surfaces.

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Safety Data Sheet (SDS).

Direction For Use

Application

A thorough cleaning of the substrates is essential to achieve serviceable adhesion on metals, plastics and coated surfaces.

1. Apply a thin and even layer of TEROSON® SB 450 using

suitable clean cloth or paper.

2. Wipe surfaces when still wet to remove all heavy contamination. If necessary, repeat cleaning process.
3. The cloth or paper should be changed after apparent contamination.
4. Allow TEROSON® SB 450 to fully evaporate from parts prior to bonding to avoid solvent entrapment within the bond joint.
5. Apply the Henkel adhesive immediately after drying and assemble bond.
6. In order to ensure TEROSON® SB 450 covers the entire substrate, the product contains a UV indicator. It is particularly well visible under a UV lamp with a wavelength of approx. 380 nm.
7. Close the container tightly after use to prevent access of humidity. With exposure to water/humidity TEROSON® SB 450 loses its activity and becomes cloudy.

Cleaning

Splashes should be removed immediately with an absorbing material.

Handling Precautions

Cleaner must be handled in a manner applicable to highly flammable materials and in compliance with relevant local regulations.

Special care must be taken to avoid contact of the product or its vapour with naked flame or any electrical equipment that is not flame proofed.

The solvent can affect certain plastics or coatings. It is recommended to check all surfaces for compatibility before use.

Storage

The product is classified as flammable and must be stored in an appropriate storage area in compliance with relevant regulations. Do not store near oxidizing agents or combustible materials. Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

Optimal Storage: 10 to 25 °C. Storage below 10 °C or greater than 25 °C can adversely affect product properties.

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Henkel representative.

Product Specification

The technical data contained herein are intended as reference only and are not considered specifications for the

product. Product specifications are located on the Certificate of Analysis or please contact Henkel representative.

Approval and Certificate

Please contact a Henkel representative for related approval or certificate of this product.

Data Ranges

The data contained herein may be reported as a typical value. Values are based on actual test data and are verified on a periodic basis.

Temperature/Humidity Ranges: 23 °C / 50% RH = 23±2 °C / 50±5% RH

Disclaimer:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombian, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation or Henkel Canada, Inc. the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume

responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere.® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference **N/A**